

GLENDO LLC

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

MATERIAL NAME: TAP MAGIC

TRADE NAME: Tap Magic
PART NUMBERS: 004-638
DISTRIBUTOR'S NAME: Glendo LLC
ADDRESS: 900 Overlander Road, Emporia, KS 66801
PHONE: (620) 343-1084

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>CHEMICAL NAME</u>	<u>CAS #</u>	<u>OSHA PEL, ppm</u>	<u>ACGIH TLV</u>	<u>Other Limits Recommended</u>	<u>Max %</u>
PETROLEUM DISTILLATE (ALIPHATIC 90%/AROMATIC 10%)	8008-20-6	NOT LISTED	NOT LISTED	est. TLV 1000 ppm	60
METHYL LAURATE	111-82-0	NOT LISTED	NOT LISTED		40
VEGETABLE OIL, ESSENTIAL	8007-80-5	NOT LISTED	NOT LISTED		10

3. HAZARDS IDENTIFICATION

ROUTES OF ENTRY: Ingestion is the primary method of possible entry. Material will not pass the skin barrier. Inhalation is unlikely due to low vapor pressure.

EFFECTS OF ACUTE OVEREXPOSURE

INHALATION: Concentration in excess of 1000 ppm may cause headache, nasal and respiratory irritation, nausea, drowsiness, fatigue, eye irritation and central nervous system depression. Narcotic effects may be severe at concentrations greater than 20,000 ppm.

SKIN CONTACT: Material will not pass the skin barrier.

INGESTION: Headache, drowsiness, nausea, fatigue, CNS depression.

EYE: May cause pain and irritation.

EFFECTS OF CHRONIC OVEREXPOSURE

SKIN CONTACT: Prolonged or repeated exposure may cause defatting of the skin and subsequent rash or irritation.

ALL ROUTES OF ENTRY: Based on available data, repeated exposures are not anticipated to cause any significant adverse effects. Birth defects are unlikely. Exposures having no adverse effects on mother should have no effect on the fetus. In animal studies, has been shown not to interfere with reproduction. Results of in vitro ("test tube") mutagenicity tests have been negative. Results of mutagenicity tests in animals have been negative.

CARCINOGENICITY: Does not cause cancer in long term animal studies. Not a carcinogen or suspect carcinogen.

WARNING: Any cutting fluid can be "overworked" or "overheated", causing it to break down. This overuse is identified by the sight of or strong odor of vapors or fumes not normally present. The effects of these vapors or fumes on human health have not been fully determined. After use of this product, clean and lubricate metal surfaces to avoid staining and/or corrosion.

4. FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES

EYE: Flush eyes gently with water for at least 15 minutes. Supportive treatment by a physician is recommended.

SKIN: Wash with mild soap and water. Remove wetted clothing until dry.

INHALATION: Remove to fresh air. Individuals showing pronounced anesthetic effects may require artificial respiration and oxygen.

INGESTION: Do not induce vomiting. Call a physician and/or transport to emergency medical facility immediately.

NOTES TO PHYSICIAN: oral: low in toxicity. Emetics are contraindicated due to danger of aspiration. If CNS depression is prominent, nikethamide may be given parenterally. Avoid epinephrine. If and when warranted by special circumstances, gastric lavage may be performed cautiously with 3% sodium bicarbonate or water. Instill 30 to 60 ml of olive oil in the stomach at the conclusion of lavage and follow with a saline cathartic (sodium sulfate) in water.

5. FIRE, EXPLOSION DATA AND MEASURES

LOWER FLAMMABLE LIMIT IN AIR (% BY VOLUME): 0.7

UPPER FLAMMABLE LIMIT IN AIR (% BY VOLUME): 5.0

FLASH POINT, PMCC: 185°F

AUTOIGNITION TEMPERATURE: 450°F

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical

6. ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES

SMALL SPILLS: Absorb with inert material (saw dust, rags, activated charcoal). Remove to out of doors and incinerate.

LARGE SPILLS: Evacuate area. Contain liquid; transfer to closed metal (steel) containers. Keep out of water supply. Protect from ignition sources.

NEUTRALIZATION CHEMICAL: Product may be effectively absorbed with activated charcoal.

7. HANDLING AND STORAGE

Shelf life is indefinite at ambient temperatures and left in original containers. It is a combustible liquid, keep away from open flames. Do not ingest. Do not expose to ignition sources. Do not store with any strong oxidizers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Normal ventilation with regular use to maintain vapor concentration below 1000 ppm.

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT (PPE):

RESPIRATORY: None during normal use. Up to 2500 ppm, half-mask organic vapor respirator. Up to 5000 ppm, full-face organic vapor respirator, or full-face supplied air respirator. Greater than 5000 ppm, fire fighting or unknown concentration, self-contained breathing apparatus with positive pressure.

EYES: None during normal use; face shield is recommended during machining operations.

SKIN: None required for casual contact during normal use. Nitrile, neoprene or other petroleum distillate resistant gloves and/or boots recommended for dealing with large spills.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Light yellow liquid

ODOR: Pleasant

SPECIFIC GRAVITY (WATER = 1) (LBS/GAL): 0.824 (6.88)

VAPOR PRESSURE (MM OF MERCURY) @ 75°F: Less than 5

VAPOR DENSITY (AIR = 1): 5.5

SOLUBILITY IN WATER, % BY WEIGHT: Less than 1 (Insoluble)

EVAPORATION RATE (BUTYL ACETATE = 1): 0.04

% VOLATILE BY VOLUME @ 75°F: Less than 1

PH: Neutral (Non aqueous)

BOILING RANGE (760 MM, MERCURY): 370 to 560°F

10. STABILITY AND REACTIVITY

STABILITY: Chemical stability is very good; odor and color may be adversely affected by prolonged storage in hot, moist environment.

INCOMPATIBILITY: May cause swelling of some plastics and synthetic rubbers. Contact with strong oxidizing agents should be avoided. (Example: Oxygen gas under high pressure.)

HAZARDOUS DECOMPOSITION PRODUCTS: None, Incomplete combustion can yield carbon monoxide.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: None

11. TOXICOLOGICAL INFORMATION

INGESTION LD50: for rabbits is 28g/kg; estimated toxic adult dose 3-4 oz.

12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY: Aquatic toxicity is low: Product is not soluble in water.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Small amounts may be incinerated in compliance with local, state and federal regulations. The recommended method of disposal for large quantities is recycling by a reclaimer or incineration. If inert absorbents are employed in spill containment or cleanup, these absorbents must be non-biodegradable materials if destined for landfill disposal. Suitable absorbents include natural minerals (clay), activated charcoal, man-made polymers (HD polyethylene).

14. TRANSPORT INFORMATION

Tap Magic is in compliance with all of the requirements of the TSCA at the time of shipment.

15. REGULATORY INFORMATION

Tap Magic Aluminum DOES NOT CONTAIN 1,1,1-trichloroethane, or any ozone depleting substances. Tap Magic Aluminum does not contain nitrites, nitrite derivatives, amines, polynuclear aromatic compounds either as an ingredient or a trace contaminant. Shelf life is indefinite at ambient temperatures and left in original containers. Tap Magic does not contain any chemical compound listed on the SARA list of "Extremely Hazardous Chemicals."

16. OTHER INFORMATION

The information contained herein is based on data considered to be accurate; however, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third party persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the material safety data sheet.

Additionally, vendor assumes no responsibility for injury to vendee or third party persons proximately caused by abnormal use of this material even if reasonable safety procedures are followed.

Vendee assumes the risk in use of this material.

CREATION DATE	CREATED BY	
03/2002	B. Teegardin	
REVISION DATE	REVISED BY	REASON FOR REVISION
06/10/2013	A. Henson	Content Review
08/13/2014	R. Fessler	Content Review